



P.O. Box 1789 • Amarillo, TX 79105      806-622-1273  
2401 Sundown Lane, 79118      Fax: 806-622-3258  
www.amarillogear.com      E-mail: info@amarillogear.com

### Amarillo "A" Series Fan Drives for Cooling Towers

**Optional Features - to be added to  
list price of standard drives NOTE 4**

MODEL	LIST PRICE <small>NOTE 1</small>	OIL HEATER & THERMOSTAT	OIL LEVEL SWITCH <small>NOTE 2</small>	NON REVERSE	LOW SPEED OPTION (NET) <small>NOTE 3</small>	SYNTHETIC OIL (NET)	304SS BALL VALVE (NET)	EXPORT BOX (NET) <small>NOTE 5</small>
<b>A20</b>	4,290	NA	960	1,980	470	70	70	60
<b>A22</b>	6,140	NA	960	1,980	510	190	70	70
<b>A27</b>	11,860	CF	960	2,200	570	520	70	140
<b>A32</b>	22,290	600	960	2,640	NA	890	100	330
<b>A34</b>	30,700	930	960	2,640	NA	1,110	100	430
<b>A36</b>	36,390	930	960	2,640	NA	1,110	100	430
<b>A38</b>	39,860	930	960	2,640	NA	1,110	100	430

**Prices of all Amarillo Drives are EXW, Amarillo, Texas  
Prices Subject to Change without Notice**

NA: Not Available  
CF: Contact Factory

#### Notes:

- Prices are for standard rotation and standard ratios as listed in our current catalog. For special paint, special rotation, or special output shaft requirements, please contact the factory.
- Oil level switch is CSA listed for hazardous location: Class 1, Div. 1, Groups C & D. Switch is rated 10 amps @ 125 VAC. SPDT is standard. DPDT is available for an additional \$110 list.
- Low Speed Option is a proprietary modification to the single reduction gearbox that allows for no minimum" input (motor) speed when used in conjunction with Variable Frequency Drives (VFD). The minimum input (motor) speed without the Low Speed Option is 450 rpm. Input (motor) speed less than 450 rpm on double reduction gearboxes will require the Electric Oil Pump option.
- Optional equipment and features may add to delivery time.
- Export boxes are made with heat treated lumber.